

AVALANCHE

Bottled Water Cooler




Crystal Mountain™

AVALANCHE

Bottled Water Cooler


The small footprint Avalanche water cooler is designed to fit conveniently on a kitchen or office countertop. The compressor in this compact design provides exceptional cooling rates and runs very quietly. Depending on the market, this cooler comes in Cold only, dual Chill and Hot and Cold models and has handy LED lights indicating when water reaches temperature. Also available as a Point-of-Use (Plumbed In) unit.

Features & Benefits

- Carrying handle makes dispenser easy to carry
- LED display indicates when cold and hot water are at the optimum temperature
- Small footprint conveniently fits kitchen or office
- Compressor operated for efficient water temperature recovery
- Stainless steel reservoir
- One piece drip tray is dishwasher safe



Carrying handle



LED display

DryGuard™

Crystal Mountain's patented sealed-system DryGuard™ feature, molded from polypropylene, protects floors against leaks caused by cracked and faulty bottles.



AVALANCHE

Bottled Water Cooler

Performance & Specification

General

Air cooled, bottled type water cooler provided with a power supply cord

Cooler Cabinet

Blow molded, high density polyethylene(HDPE)
Together with injection molded bottom plate

Faucet Type

Constructed of FDA approved nylon and silicon tubing
Childproof Hot water faucet

Cold Water Tank Specifications

HDPE casing with 1.8L (0.5 gal) volume
Cold water cooling capacity of 3.5L (0.9 gal)/hour based on 21°C (69.8°F) room temperature

Cold Water Thermostat

Preset at factory to dispense water at temperature from 2-10°C (35.6-50°F)
Adjustable cold control located at the back of the cabinet

Hot Water Tank Specifications

Stainless steel #304 casing with 1.4L (0.4 gal) volume
Hot tank capacity 4.5L (1.2 gal)/hour based on 21°C (69.8°F) room temperature

Hot Water Thermostats & Heater

Automatic thermostat set at temperature range of 75-92°C(167-197.6°F)
Manual thermostat reset in case of automatic thermostat failure
ON/OFF switch for hot tank is located at the back of the cabinet

Compressor

Hermetically sealed reciprocating compressor
(220~240VAC 50Hz) (100~115VAC 60Hz)

Refrigerant Type: R134a (CFC Free)

Refrigerant Charge: 28.4g (1.0 oz)

Dimensions & Freight Data

Product Dimensions

368mm deep x 330mm wide x 419mm high
(14.5" deep x 13.0" wide x 16.5" high)

Product Weight

H&C: 11.3kg (24.8 lb)
C&C: 10.5kg (23.1 lb)
Cold Only: 10.3kg (22.7 lb)

Product Boxed Dimensions

380mm deep x 370mm wide x 450mm high
(15.0" deep x 14.6" wide x 17.7" high)

Product Boxed Weight:

H&C: 12.6kg (27.8 lb)
C&C: 11.8kg (26.0 lb)
Cold Only: 11.6kg (25.6 lb)

20FT Container Quantity: 450 Units

40FT Container Quantity: 960 Units



All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.



AVALANCHE



Website: www.crystalcoolers.com

Crystal Mountain Products Limited

North American Sales Office

18136-102 Avenue
Edmonton, Alberta
Canada T5S 1S7
Tel: 1 800 878 6422
Tel: 1 780 454 4545
Fax: 1 780 454 9816
E-mail: cmcanada@crystalcoolers.com

European Sales Office

Signature House, Gunco Lane
Macclesfield, Cheshire
United Kingdom SK11 7JL
Tel: 44(0) 1625 439 111
Fax: 44(0) 1625 508 625
E-mail: cmeurope@crystalcoolers.com

Crystal Mountain International Limited

Hong Kong Sales Office

Room 610, Winfield Commercial Building
6-8a Prat Avenue, Tsimshatsui
Kowloon, Hong Kong
Tel: (852) 2368 1989
Fax: (852) 3017 6727
E-mail: cmasia@crystalcoolers.com

CE  US LISTED CB  SASO ISO9001 WEEE RoHS

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

AVB REV0509